

**AROMA IST-4-027567****D05*****Target Scenarios specification: vision at project stage 1***

Contractual Date of Delivery to the CEC: 31-03-2006

Actual Date of Delivery to the CEC: 05-04-2006

Editor: Rickard Ljung and Anders Dahlen (TEL)

Author(s): See list

Participant(s): UPC, KCL, PTIN, TI, TID, TEL, IST-TUL

Workpackage: WP1

Est. person months: 9

Security: PU

Nature: R

Version: 001

Total number of pages: 125

Abstract:

This deliverable selects some scenarios of interest (in terms of cellular structure, propagation and user-mobility models, Radio Access Technology considered, etc...), identifies the key parameters of the assumed services; defines the QoS parameters required of each for the services (e.g. packet delay, jitters, losses, etc) and maps these services onto bearer services.

Keyword list: Scenarios, Mobility and Propagation models, Layouts, Traffic Characterization, Traffic mix, QoS parameters

DISCLAIMER

The work associated with this report has been carried out in accordance with the highest technical standards and the AROMA partners have endeavoured to achieve the degree of accuracy and reliability appropriate to the work in question. However since the partners have no control over the use to which the information contained within the report is to be put by any other party, any other such party shall be deemed to satisfied itself as to the suitability and reliability of the information in relation to any particular use, purpose or application.

Under no circumstances will any of the partners, their servants, employees or agents accept any liability whatsoever arising out of any error or inaccuracy contained in this report (or any further consolidation, summary, publication or dissemination of the information contained within this report) and/or the connected work and disclaim all liability for any loss, damage, expenses, claims or infringement of third party rights.

DOCUMENT HISTORY

Date	Version	Status	Comments
2006-01-15	001	Int	First draft of proposed ToC
2006-02-21	002	Int	Revised ToC
2006-03-02	003	Int	Revised ToC
2006-03-09	004	Int	First version for comments and additions
2006-03-14	005	Int	Revised version for comments and additions
2006-03-15	006	Int	Revised version for comments and additions
2006-03-22	007	Int	Draft final version
2006-03-24	008	Int	Revised draft final version
2006-03-31	009	Int	Version for PCC review
2006-04-05	001	Apr	Approved version

Authors List

Andrea Barbaresi (TI)
Paola Bertotto (TI)
Fernando Casadevall (UPC)
Luis M. Correia (IST-TUL)
Robert Farotto (TI)
Ramón Ferrús (UPC)
Hiram Galeana (UPC)
Gabriela Galvano (IST-TUL)
Álvaro Gomes (PTIN)
Beatriz Gonzalez (TID)
Peter Karlsson (TEL)
Matijn Kuipers (IST-TUL)
Rickard Ljung (TEL)
Andrea Mantovani (TI)
Nima Nafisi (KCL)
Avelina Vega Novella (TID)
Joan J. Olmos (UPC)
Jordi Pérez-Romero (UPC)
Oriol Sallent (UPC)
Antonio Serrador (IST-TUL)

EXECUTIVE SUMMARY

The scope of this document is to define and characterize the target scenarios to be addressed during the first year of the AROMA project, focusing on those parameters that are relevant for the Radio Resource and QoS management for cellular heterogeneous networks. The heterogeneous network comprises 2G and 3G cellular systems as well as wireless local area networks (WLANs).

The scenarios are mainly based on the requirements and visions of the four operators in the project, and they are described by four main items, which are considered most relevant for RRM strategies within cellular heterogeneous networks. The vision encompasses a heterogeneous network and users with multimode mobile terminals in the time frame of 2009-2010.

After a short introduction, the document gives in section 2 an overview of the scenarios that will be used within AROMA. Section 3 presents the reference QoS architecture assumed, which is well aligned with the work carried out in 3GPP. The characterization of the Radio Access Technologies (RAT) is done in Section 4 whereas Section 5 addresses to the service characterization, including some figures about the offered traffic predictions and traffic loads measurements. In section 6 the main characteristics of the environments to be assumed in AROMA: Dense Urban; Urban; Suburban and Indoor "Hot Spot", are described including user mobility and user density models as well as Radio Access Network (RAN) infrastructure deployment. The transport network characterization for both the radio access part and the core network is done in section 7, whereas the description of the final selected scenarios, considering both theoretical and realistic, is done in section 8. Finally section 9 contains a brief conclusion about the document.

To conclude this executive summary, it is not worthless to indicate that the selected scenarios and the corresponding evaluation procedures are compliant with 3GPP specifications in order to facilitate the impact of the project result in 3GPP.

Table of Contents

EXECUTIVE SUMMARY	V
1 INTRODUCTION	1
2 SCENARIO OVERVIEW	1
3 REFERENCE ARCHITECTURE	2
3.1 3GPP REFERENCE FRAMEWORK.....	2
3.1.1 3GPP R6 Network Architecture.....	2
3.1.1.1 UTRAN and GERAN.....	2
3.1.1.2 WLAN Interworking.....	4
3.1.1.2.1 3GPP WLAN subsystem.....	4
3.1.1.2.2 GAN: Generic Access to A/Gb Interfaces.....	5
3.1.2 3GPP System evolution architecture (SAE) and UTRAN long term evolution (LTE).....	6
3.1.2.1 SAE/LTE description.....	8
3.1.2.1.1 Siemens proposal [9].....	9
3.1.2.1.2 Ericsson proposal [10].....	11
3.1.2.1.3 Qualcomm proposal [11].....	13
3.1.2.1.4 NTT DoCoMo, Alcatel, CATT, ETRI, Fujitsu, Huawei, IPWireless, LG Electronics, Lucent, NEC, Nokia, Nortel, Panasonic, Samsung, Toshiba joint proposal [12].....	16
3.1.2.2 Interworking with legacy systems.....	17
3.1.3 Pre-commercial solutions of Evolved Network Architecture.....	18
3.1.3.1 Nokia proposal [19].....	18
3.1.3.2 Cisco proposal [50].....	19
3.2 AROMA ALL-IP REFERENCE NETWORK ARCHITECTURE.....	20
3.2.1 IP-based RAN.....	20
3.2.2 Medium-Term vision.....	24
3.2.3 Long-Term vision.....	26
4 RADIO ACCESS TECHNOLOGIES: CHARACTERIZATION	27
4.1 RAT CHARACTERISTICS.....	27
4.1.1 Link budget.....	27
4.1.2 Frequency allocation.....	28
4.2 RADIO ACCESS BEARERS.....	29
4.2.1 RABs in UTRAN.....	29
4.2.2 RABs in GERAN.....	31
4.2.2.1 Initial Considerations.....	31
4.2.2.2 GPRS RABs.....	32
4.2.2.3 EDGE RABs.....	32
4.2.2.4 Multislot capability.....	33
4.2.3 RABs in WLAN.....	34
4.2.4 RAB for VoIP.....	37
4.2.5 RAB Summary.....	38
4.2.6 RAB power levels.....	39
4.3 RADIO ACCESS DELAYS.....	43
4.3.1 Radio bearer establishment in 3GPP release 99.....	44
4.3.1.1 GPRS 2G.....	44
4.3.1.1.1 Mobile Originated Packet Access.....	44
4.3.1.1.2 Mobile Terminated Packet Access.....	44
4.3.1.2 UMTS.....	44
4.3.1.2.1 Mobile Originated Packet Access.....	44
4.3.1.2.2 Mobile Terminated Packet Access.....	45
4.3.2 GPRS 3G RRC Connection Establishment.....	47
4.3.3 GPRS 3G Radio Bearer Establishment.....	47
4.3.4 Example of connection setup delays.....	48
4.3.5 UTRAN to GERAN inter-RAT handover.....	49
4.3.5.1 Procedures in UTRAN to GERAN inter-RAT handover.....	49
4.3.5.2 Example of UTRAN to GERAN inter-RAT handover delays.....	51
5 SERVICES	52
5.1 SERVICE MIX.....	52

5.2	MULTIMEDIA BROADCAST / MULTICAST SERVICE (MBMS)	55
5.2.1	<i>MBMS Services</i>	56
5.2.1.1	Classification of MBMS User Services	57
5.2.1.2	Services examples	58
5.2.1.3	Service scenarios examples	60
5.2.2	<i>Network Architecture</i>	61
5.3	SERVICE CHARACTERIZATION	64
5.3.1	<i>VoIP service model</i>	64
5.4	SPECIFICATION OF QOS PARAMETERS	67
5.5	TRAFFIC LOAD MEASUREMENTS	68
5.5.1	<i>GPRS</i>	68
5.5.2	<i>WLAN</i>	69
6	ENVIRONMENTS	69
6.1	USER CATEGORIES	69
6.2	USER MOBILITY	71
6.2.1	<i>Mobility models for ideal scenarios</i>	71
6.2.1.1	Suburban and urban environment	71
6.2.1.2	Dense urban environment	72
6.2.2	<i>Mobility model for realistic scenarios</i>	74
6.3	RADIO WAVE PROPAGATION	75
6.3.1	<i>General Modeling</i>	75
6.3.2	<i>Macrocell propagation</i>	76
6.3.2.1	UMTS path loss	76
6.3.2.2	GERAN, path loss	76
6.3.2.3	Ray tracing model for Macrocell propagation (Ma3)	77
6.3.2.4	Diffraction model for macrocell environment	77
6.3.2.5	Correction factors for macrocell environment	78
6.3.2.5.1	Building density	78
6.3.3	<i>Microcell propagation</i>	80
6.3.3.1	UMTS path loss	80
6.3.3.2	GERAN path loss	81
6.3.3.3	WLAN path loss	83
6.3.4	<i>Ray tracing model (Mi3)</i>	84
6.3.5	<i>Indoor propagation</i>	85
6.3.5.1	UMTS path loss	85
6.3.5.2	WLAN, path loss	86
6.3.5.3	Indoor Empirical Propagation Model (In3)	86
6.3.5.3.1	Distance dependence of path loss exponent	86
6.3.5.3.2	Angle dependence of Attenuation Factors	87
6.3.5.3.3	Diffraction	87
6.3.6	<i>Outdoor to Indoor propagation</i>	88
7	TRANSPORT NETWORK CHARACTERISATION	88
7.1	RADIO ACCESS NETWORKS	88
7.1.1	<i>RAN Topologies</i>	89
7.1.2	<i>RAN Transport Reference Architecture</i>	90
7.1.2.1	Urban Scenario	90
7.1.2.2	Rural Scenario	91
7.2	CORE NETWORK	91
7.2.1	<i>Core Network Topologies</i>	92
7.2.2	<i>CN Transport Reference Architecture</i>	92
8	TARGET SCENARIOS	93
8.1	THEORETICAL SCENARIO	93
8.1.1	<i>Hotspot within urban area</i>	93
8.1.1.1	MIMO modeling for hotspot within urban area	96
8.1.2	<i>Hot spot along main road</i>	96
8.1.2.1	MIMO modelling for hotspot along main road	98
8.1.3	<i>Urban residential area</i>	98
8.1.3.1	MIMO modeling for urban residential area	100
8.2	REALISTIC SCENARIO	101
8.2.1	<i>Urban/Suburban</i>	101
8.2.1.1	Description of the realistic scenario and choice of the statistic cells	101
8.2.1.2	Radio resource parameters configuration	106

- 8.2.2 *Dense urban* 108
- 8.2.3 *Multifloor building*..... 110
- 9 CONCLUSIONS** **112**
- ABBREVIATIONS**..... **114**
- ANNEX: DETAILS ON TRANSPORT NETWORK CHARACTERISATION** **117**
- A.1 *Transport Solutions for RANs*..... 117
- A.2 *Transport Solutions for CN* 120
 - A.2.1 SONET/SDH121
 - A.2.2 ATM over SONET/SDH.....121
 - A.2.3 Packet over SONET (POS).....122
 - A.2.4 POS without SONET/SDH122
 - A.2.5 Gigabit Ethernet.....122
 - A.2.6 Dark fiber services123
- REFERENCES** **124**